

Gylon 3504 Gasket Material



Compressed Fibre Gasket Sheets



Filled PTFE Gaskets and Sheet



Premium Rubber Gaskets and Sheets



Gasket Cutting Tools and Accessories

AG Sydney Head Office 02 9774 3333

syd@agaus.com.au

Offers superior performance over conventional PTFE providing a tight seal with reduced emissions and excellent bolt torque retention.

Will withstand attack from an extremely wide range of chemicals which making it able to provide a superior service life in a wide variety of applications.

Also known as Blue Gylon, Gylon 3504 utilises aluminosilicate microspheres to create a gasket material that excels in sealing moderate concentrations of acids, caustics, hydrocarbons, refrigerants and more.

Standrd Sizes		
Standard Thicknesses:	0.8mm 1.5mm & 3mm	
Maximum Sheet Size:	1500mm x 2286mm	

Other sizes and thicknesses available on request.

For custom sheets, cut gaskets, pricing, availablility and more information; please do contact your local Associated Gaskets Branch.

ER P. TEL & CHELUCE	TEST.	UN DBA BASKETS
JN USA BASKEYS	GYL	LON JUSH SASKEYS

Key Specifications		
Contrusction	PTFE w/ aluminisilicate	
Max. Temperature	260°C	
Min. Temperature	-268°C	
Max. Pressure	55 bar 797 psi	
Compressibility	25% - 45%	
Recovery	30%	
Creep Relaxation	40%	
Density	1.7 g/cm³	









AG Queensland

07 3257 1144

AG Victoria

03 9768 3113

AG Western Australia AG Newcastle

08 9258 5858

02 4967 7677

AG Wollongong

woll@agaus.com.au

02 4272 4800

bris@agaus.com.au melb@agaus.com.au perth@agaus.com.au new@agaus.com.au