




Neoprene Closed Cell Sponge Sheet (CR160)

This high-quality sponge rubber displays excellent resistance to oils, solvents and many chemicals.

This material is self-extinguishing, and is used as cushioning, expansion joints, insulation or weatherproof door seals.

Available with or without an adhesive backing, this versatile and economical material can be supplied in sheets, cut gaskets, strips, washers and all manner of custom made components.


Our Neoprene Sponge Sheet creates watertight seals at low bolt loads.




Sponge & Foam Sealing Tapes



Rubberised Sponge & Foam Gasket Sheets



Rubber Sheets



Rubber & Sponge Extrusions

Typical Applications.

- Cabinet & hatch seals
- Expansion joints
- Door & window seals
- Surface protection
- Low pressure gaskets
- Weather & gap seals
- Light & dust seals
- Anti-Vibration pads



Key Specifications

Max. Temperature	80°C
Density	160 kg/m ³
Hardness	25 HS Type C
Tensile Strength	4 kg/cm ² (min.)
Water Absorption	< 4%

Standard Sizes

2mm	3mm	4mm	5mm
6mm	8mm	10mm	12mm
18mm	20mm	25mm	30mm

Full Sheets are 1000mm x 2000mm

Additional Thicknesses can be Laminated.

AG Sydney
Head Office
02 9774 3333

syd@agaus.com.au

AG Queensland
07 3257 1144

bris@agaus.com.au

AG Victoria
03 9768 3113

melb@agaus.com.au

AG Western Australia
08 9258 5858

perth@agaus.com.au

AG Newcastle
02 4967 7677

new@agaus.com.au

AG Wollongong
02 4272 4800

woll@agaus.com.au

Visit agaus.com.au for more information and full contact details.