



Weicon Concrete Repair Stick

The Concrete grade of epoxy repair putty featured on this page is particularly useful for quick repairs and reconditioning work to concrete, stone and ceramic surfaces.

Repair Stick Concrete is manufactured from epoxy resin with ceramic fillers and, once fully cured, is concrete-grey in colour.

It is often used for filling and closing cracks as well as repairing defects on:

- Masonry
- Stone slabs, concrete slabs and tiles
- Bricks
- Borders and curbstones
- Statues and ornaments
- As well as for fixing pegs, screws and anchors in both indoor and outdoor environments.



Epoxy Repair Sticks



Plastic Metal





Epoxy Adhesives



Putties & Compounds

Key Specifications	
Colour	Grey
Density	1.9 g/cm ³
Pot Life	6 Minutes
35% Cure	15 Minutes
Full Cure	24 Hours
Shore Hardness	80 Shore D
Temperature Resistance	-50°C to +120°C
Avg. Tensile Shear Strength	4.8 N/mm ² on Concrete

Standard Sizes	
57gm	115gm



AG Sydney
Head Office
02 9774 3333

syd@agaus.com.au

AG Queensland

07 3257 1144

bris@agaus.com.au

AG Victoria

03 9768 3113

melb@agaus.com.au

AG Western Australia

08 9258 5858

perth@agaus.com.au

AG Newcastle

02 4967 7677

new@agaus.com.au

AG Wollongong

02 4272 4800

woll@agaus.com.au

Visit agaus.com.au for more information and full contact details.