



## Weicon Flex 310 M HT 200



**MS Polymer  
Adhesives &  
Sealants**



**Cleaners and  
Surface  
Preparation**



**Primers &  
Bonding Aids**



**Dispensing  
Equipment &  
Tools**

A high temperature resistant grade of elastic adhesive designed specifically for bonding parts that will be subjected to elevated thermal stress.

This one part adhesive is manufactured from a MS polymer base and bonds well to most materials.


Once fully cured, parts bonded and/or sealed with Weicon Flex 310 M HT 200 can be powder coated.

Available in 310ml cartridges that work with any standard caulking gun, this quality adhesive sealant exhibits high adhesive power, good elasticity and long lasting performance.

HT 200 is manufactured in Germany and can withstand temperatures up to 200°C for 30 minutes. It has a pasty viscosity and is easy to apply accurately to vertical or horizontal surfaces.



Key Specifications	
Density	1.41 g/cm <sup>3</sup>
Viscosity	Pasty
Cure Speed	3-4mm (first 24 hours)
Skin-Over	10 Minutes
Elongation at Break	400%
Shore Hardness	55 Shore A
Temp. Resistance Continuous	-40°C to +90°C
Temp. Resistance (30 Minutes)	+200°C



**Available in 310ml Cartridges.**

AG Sydney  
Head Office  
02 9774 3333

[syd@agaus.com.au](mailto:syd@agaus.com.au)

AG Queensland

07 3257 1144

[bris@agaus.com.au](mailto:bris@agaus.com.au)

AG Victoria

03 9768 3113

[melb@agaus.com.au](mailto:melb@agaus.com.au)

AG Western Australia

08 9258 5858

[perth@agaus.com.au](mailto:perth@agaus.com.au)

AG Newcastle

02 4967 7677

[new@agaus.com.au](mailto:new@agaus.com.au)

AG Wollongong

02 4272 4800

[woll@agaus.com.au](mailto:woll@agaus.com.au)

Visit [agaus.com.au](http://agaus.com.au) for more information and full contact details.