



Pure Gum Rubber 35 Duro

Pure Gum is a natural, soft rubber that is very flexible and has excellent resistance to wet and dry fine particle sliding abrasion. Commonly used for chute lining, conveyor curtains, and surface protection, it possesses excellent wear and sealing characteristics. Due to it not containing any colour pigmentation or synthetic compounds, Gum rubber is non-marking, and perfect for those critical applications where colour contamination may be an issue.

Technical Data:

Property:	Value:	Test Method:
Polymer	NR	---
Colour	Translucent/Tan	---
Temperature Range	-25° to + 70°C	---
Specific Gravity	0.97	ASTM D297
Hardness	35 ± 5 Shore A	ASTM D2240
Tensile Strength	15 MPa min	ASTM D412
Tear Strength	60 N/mm min	ASTM D624
Elongation at Break	700% min	ASTM D412

Applications:

- Flexible Sleaving
- Gaskets and Seals
- Flexible Skirting
- Surface Protection
- Chute Lining
- Isolation Barriers
- Dust Covers
- Funnels and Chutes

Availability:

Associated Gaskets stock a large range of specialised rubbers to suit most requirements. Gum Rubber is available in a variety of thicknesses, 1200mm wide x 10m long rolls, and is sold by the metre, the roll, or can be cut or slit to suit your specifications.

AG also stock an extensive range of gasket material including most grades of rubber, compressed fibre, PTFE, and high temperature materials.

For more information on these products and many more, please visit our website or call your nearest AG branch.

Visit: www.agaus.com.au

Phone: 1300 098 060

Important

This information should not be treated as a substitute for specific technical advice. AG does not offer such advice and cannot warrant the performance or suitability of products for particular applications.