



Weicon Electro Contact Cleaner Fluid

Weicon Electro Contact Cleaner Fluid is specially designed for the fast and efficient cleaning and degreasing of soiled or corroded contacts of all kinds. Manufactured from a special formulation of high purity solvents, Electro Contact Cleaner effectively removes oxide or sulphide layers, combustion residues and resinous or sooty soiling from electronic or mechanical parts and evaporates without leaving any residue.

Electro Contact Cleaner not only helps to reduce voltage loss but also increases electrical conductivity. Contamination that can cause tracking is also removed. This easy to use cleaner is used for the cleaning and degreasing of a wide range of components. Examples include measuring instruments, balances, switches, sensors, electrical connections, contacts, relays and switchboards.

Properties

Colour	Clear
Odour	Almost Odourless
Temperature Resistance	---
Minimum Shelf Life	24 Months

Compatible With

Weicon WSD 400
Pressurised Air Dispenser

Preparation of the Surface

Before using Electro Contact Cleaner, disconnect or fully power-down electrical devices and wait a few minutes to ensure there is no more electric tension inside the device.

Processing

If applying using spray equipment, spray a sufficient quantity of Electro Contact Cleaner onto the parts or surface being cleaned from a distance of about 25-30cm. If applying with a rag or cloth, follow the same process except with direct contact. Electro Contact Cleaner evaporates quickly and does not leave any residue. Wiping or brushing the cleaning agent will enhance the cleaning effect.

Devices should only be switched back on when the active substance has completely evaporated.

Storage

Containers of Weicon Electro Contact Cleaner Fluid should be stored away from direct sunlight and not exposed to temperatures exceeding 50°C. Minimum shelf life is 24 months.

Availability

Weicon Electro Contact Cleaner Fluid is available in 5L, 10L or 30L containers.

Visit: www.agaus.com.au

Phone: 1300 098 060

Important

This information should not be treated as a substitute for specific technical advice. AG does not offer such advice and cannot warrant the performance or suitability of products for particular applications.