



THREADLOCKING

### WEICONLOCK 302-43



- Medium strength threadlocker.
  - Low viscosity.
  - Approved for use with gas and drinking water.
  - Can be disassembled with normal tools.
  - Suitable for threads up to M36.
- Application Examples**  
General purpose locking of threaded connections to prevent loosening.

### WEICONLOCK 302-72



- High strength threadlocker.
  - High viscosity.
  - Forms extremely strong bonds that are hard to disassemble.
  - DVGW certified for gas use.
  - Designed for high temperature applications up to 230°C.
- Application Examples**  
High performance threadlocker for critical and high temperature applications requiring an extremely strong bond.

### WEICONLOCK 302-21



- Removable threadlocker.
  - Low viscosity.
  - Forms low strength bonds that are easy to disassemble.
  - Designed for small gauge screws and parts.
  - Handling strength 5 - 15 mins.
- Application Examples**  
Perfect for protecting against vibration loosening in applications that require the connection to be undone from time to time.

### WEICONLOCK 306-03



- General purpose adhesive for retaining cylindrical assemblies.
  - Low viscosity.
  - For threaded joints up to M12.
  - Creates a permanent seal that is difficult to dismantle.
- Application Examples**  
Economical choice for sealing and locking ball, roller and slide bearings as well as bushes, bolts, liners, keys, splines and other close fitting parts.

### WEICONLOCK 306-48



- High strength adhesive for retaining cylindrical assemblies.
  - High Viscosity
  - Approved for oxygen use
  - High Temperature
  - Suitable for threads up to M20
- Application Examples**  
Sealing and locking ball, roller and slide bearings as well as bushes, bolts, liners, keys, splines and other close fitting parts, where a higher viscosity option is required.

### WEICONLOCK 306-20



- Premium adhesive for retaining cylindrical assemblies.
  - Approved for gas, water and oxygen service.
  - High Temperature resistance.
  - High Viscosity.
  - Suitable for threads up to M56.
- Application Examples**  
Sealing and locking ball, roller and slide bearings as well as bushes, bolts, liners, keys, splines and other close fitting parts in critical or high temperature applications.

CLEANING

### CLEANER SPRAY S



- Fast and effective high-powered spray cleaner.
  - Evaporates without leaving residue.
  - Cleans and degreases metal, glass and ceramic surfaces.
  - Pleasant citrus smell.
- Application Examples**  
General purpose cleaning and degreasing of a range of surface types. Perfect powerfull all-round cleaner for any workspace.

THREAD SEALING

### WEICONLOCK 302-80



- High Strength pipe and thread sealer that can be used with passive materials.
  - High Viscosity.
  - Creates bonds that are hard to disassemble.
  - High temperature resistant.
- Application Examples**  
Sealing threaded connections and pipes made from passive materials including high-alloyed steel, oxide layers, chromate layers and anodic coatings.

### WEICONLOCK 305-77



- Medium Strength pipe and thread sealer.
  - High Viscosity.
  - DVGW and AGA approved for gas and oxygen service.
  - Bond can be disassembled with normal hand tools.
- Application Examples**  
Sealing threaded connections or close fitting pipes. Used on sizes up to M80 and can be applied very accurately thanks to it's higher viscosity.

### THREAD SEAL CORD DF-175



- Threadseal cord made from 100% PTFE.
  - Economical replacement for standard thread seal tape.
  - Seals all metal and plastic threads permanently.
  - Approved for gas, oxygen and drinking water use.
- Application Examples**  
Sealing of virtually all plastic and metal threaded connections exposed to gaseous or liquid media. Replacement for standard thread seal tape.

### WEICONLOCK 305-74



- General Purpose Flange sealant and liquid gasket.
  - High Strength, high viscosity.
  - Creates bonds that are hard to disassemble.
  - Economical option suitable for the majority of applications.
- Application Examples**  
For general purpose gasketing of flanges, gear boxes and motor housings. Suitable for the majority of applications.

### WEICONLOCK 305-10



- High Strength Flange Sealant.
  - High Temp: 200°C rated.
  - AGA Approved for Gas service.
  - Extremely high viscosity for accurate application.
  - High Performance sealant and liquid gasket.
- Application Examples**  
For gasketing of flanges, gear boxes and motor housings that require high temperature resistance and high performance.

### BLACK-SEAL



- High temperature silicone sealant and liquid gasket.
  - Excellent oil and grease resistance.
  - Adheres well to metals, glass and ceramic surfaces.
  - Good UV and aging resistance.
- Application Examples**  
High strength leak proof sealing and bonding of areas that require very high oil or grease resistance.

LUBRICATION

### ANTI-SEIZE HIGH-TECH



- Metal-free assembly paste for long lasting lubrication and corrosion protection.
  - High temperature resistant.
  - NSF Approved for food and potable water applications.
  - Available as paste or spray.
- Application Examples**  
Lubricating bolts, fittings and connections in applications that require very high temperature resistance or in sensitive areas.