

Specification	Table	Internal Diameter (ID, mm)	Ring Outside Diameter (OD, mm)	# of Holes (for Full Face)	Hole Ø (mm)	PCD (mm)	Full Face OD (mm)	Matches Table(s)
BS 3063	A	89	127	4	19	146	184	D E
BS 3063	D	89	127	4	19	146	184	A E
BS 3063	E	89	127	4	19	146	184	A D
BS 3063	F	89	146	8	19	165	203	H
BS 3063	H	89	146	8	19	165	203	F
BS 3063	J	89	143	8	22	165	203	K
BS 3063	K	89	143	8	22	165	203	J
BS 3063	R	86	143	8	22	165	203	
BS 3063	S	NA	NA	NA	NA	NA	NA	
BS 3063	T	NA	NA	NA	NA	NA	NA	
B16.21 (ANSI)	150	89	136.5	4	19	152	191	
B16.21 (ANSI)	300	89	149	8	22	168	210	600
B16.21 (ANSI)	600	89	149	8	22	168	210	300
B16.21 (ANSI)	900	89	168	8	25	191	141	
B16.21 (ANSI)	1500	89	175	8	32	203	267	
DIN 2690	6	90	132	4	18	150	190	
DIN 2690	10	90	142	8	18	160	200	16 25 40
DIN 2690	16	90	142	8	18	160	200	10 25 40
DIN 2690	25	90	142	8	18	160	200	10 16 40
DIN 2690	40	90	142	8	18	160	200	10 16 25
BS 4865	2.5	90	132	4	18	150	190	6
BS 4865	6	90	132	4	18	150	190	2.5
BS 4865	10	90	142	8	18	160	200	16 25 40
BS 4865	16	90	142	8	18	160	200	10 25 40
BS 4865	25	90	142	8	18	160	200	10 16 40
BS 4865	40	90	142	8	18	160	200	10 16 25
BS 4865	64	86	148	NA	NA	NA	NA	
AS 2129	A	NA	NA	NA	NA	NA	NA	
AS 2129	C	82	122	4	18	146	185	
AS 2129	D	82	122	4	18	146	185	
AS 2129	E	82	122	4	18	146	185	
AS 2129	F	80	141	8	18	165	205	
AS 2129	H	80	127	8	18	165	205	
AS 2129	J	80	127	8	22	165	205	
AS 2129	K	80	127	8	22	165	205	
AS 2129	R	80	127	8	22	165	205	
AS 2129	S	83	114	8	26	165	205	
AS 2129	T	80	127	8	30	191	235	