

BlueGard 3000 Gasket Sheet



Compressed Fibre Gasket Sheets



Filled PTFE Gaskets and Sheet



Premium Rubber Gaskets and Sheets



Gasket Cutting Tools and Accessories

AG Sydney Head Office 02 9774 3333

syd@agaus.com.au

A quality, general-purpose grade of compressed fibre gasket sheet. Blue-Gard 3000 is made from a combination of aramid fibres and an NBR rubber binder.

This gasket material exhibits good torque retention for reliable, lasting performance. This leads to reduced leakage potential and limits waste and energy consumption.

BlueGard 3000 is available from Associated Gaskets in sheet or cut gaskets. BlueGard Gaskets can be manufactured to suit standard flanges or your custom requirements.

Standrd Sizes				
Standard Thicknesses:	0.4mm, 0.8mm 1.5mm 3mm			
Maximum Sheet Size:	1500mm x 4500mm			

Other sizes and thicknesses available on request.

For custom sheets, cut gaskets, pricing, availablility and more information; please do contact your local Associated Gaskets Branch.

	MINE A	SARE S	ELES D	SARD D			SAR
	Garlock	Garlock'	Garlock	Garlock"	600	Flores	G.
	60	60	F	600	0 0	Flange	
	3000			3000		Free	
	SALE A	BLOS A	area.	STOR A		ANTISTICK	SA
	Garlock'	Garlock	Garlock"	Garlock	Garlock	Garlock*	G
(4)	60	6 3	600	6	60	6000	1
	[3000	3000	[3000	[3000	[300		
4	NAME A	Must a	BLUE ME	SARD!	STOR -	STAR STAR STAR STAR STAR STAR STAR STAR	BA
	Garlock	Garlock	Garlock"	Garlock	Garlock*	Garlock'	G
(2)	60	60	60	() ()	6000	600	
1000	[3000	3000	[3000	[3000	3000		0
20	STEE OF STREET	SARE A	STATE OF THE PERSON NAMED IN	SARD!	SARE A	STOR STORY	BL GA
	Garlock	Garlock	Garlock	Garlock	Garlock*	Garlock"	G
(3)	F	603	60	600	E Co	600	
0000	3000	(3,000	3000	3000	3000		Ó
4	2000	1111	1111	BARD AS	BLUE CARD	BAND"	SA
	Garlock	Garlock	Garlock	Garlock	Garlock*	Garlock'	G
	6	600	600	60	600	6000	
000	[3000	[3000	3000	3000	3000		
0	ares 7	SARD!	auer d	STATE -	STATE OF	SARE!	BA
	Garlock	Garlock"	Garlock'	Garlock'	product are bonds	s and fillers in this od in an elastomer	G
	600	600	60	(Secretary	ants by improper o	ing these ingredi- cetting or handling.	
	[[3000	[[3000	3000	3000	particulates have	the potential to damage Rater to	
	MARKET AND	0180	em.	BART A	Material Sate	ty Data Sheet	BL
	Garlock	Garlock	Garlock'	Garlock	600	Cl	G
	FOR	FO	600	603	66 6.	Flange	
	3000	3000	3000	3000		Free	
	THE .	THE LAND	eren.	and A	2	ANTIONICE	SAI
	Garlock'	Garlock'	Garlock	Garlock'	Garlock*	Garlock'	G

Key Specifications				
Contrusction	Aramid with NBR			
Max. Temperature	371°C			
Min. Temperature	-73°C			
Max. Pressure	70 bar 1,000 psi			
Compressibility	8%			
Recovery	50%			
Creep Relaxation	21%			
Density	1.6 g/cm³			









AG Queensland

07 3257 1144

AG Victoria

03 9768 3113

AG Western Australia AG Newcastle

08 9258 5858

AG Newcastle 02 4967 7677

AG Wollongong

woll@agaus.com.au

02 4272 4800

bris@agaus.com.au melb@agaus.com.au perth@agaus.com.au new@agaus.com.au