



Associated Gaskets



Fibreglass and Proprietary Yarn Marigold Packings

For over 40 years AG's range of Marigold Packings have been relied on to keep valves, pumps and other equipment running efficiently and smoothly. This page presents information on just a small portion of our comprehensive range of Marigold Compression Packings so if the packing you require isn't listed here, or you need more information on one of the grades that is, please don't hesitate to contact your local AG branch.

	Construction	Temperature Rating	pH Rating	Shaft Speed Rating	Pressure Rating	Service Type
Marigold 8000T-WO	Interlock Braid	260°C	0-14	15 MPS	20 BAR Pump 124 BAR Valve	Pump & Valve
Marigold 9907	Plait Braid	500°C	2-12	10 MPS	40 BAR Pump 200 BAR Valve	Pump & Valve
Marigold 9944	Interlock Braid	280°C	2-12	10 MPS	40 BAR	Pumps

Marigold 8000T-WO

Braided from a unique combination of self lubricating, abrasion resistant yarns, Marigold 8000T-WO is a high resilience packing. This specialised grade exhibits outstanding resistance to very high shaft speeds (without scoring) and remains durable and conformable across its long service life.



Marigold 8000T-WO possesses outstanding chemical resistance and is used with media across the entire 0-14 pH scale. It is used to seal strong acids and alkalis, steam, ammonia gas, water, salt water, bromine gas, chlorine gas, petroleum, synthetic oils, solvents as well as other chemicals though it is not suited for use with strong oxidisers.

Marigold 8000T-WO is designed for use in the demanding applications found in the mining, pulp, paper and water treatment industries and is employed in both pumps and valves.

Marigold 9944

Interlock braided from volumised and slightly twisted electrical grade fibreglass yarns, Marigold 9907 is impregnated with a special blend of concentrated PTFE and a proprietary, inert, silicone-free lubricant. Used in medium temperature pump sealing applications, the PTFE lubricant used in 9944 allows it to offer very low friction during start-up and operation.

Marigold 9944 exhibits very good resistance to a range of chemicals and is used with mild acids & alkalis, steam, water, salt water, petroleum, synthetic oils, solvents and to seal abrasive slurries.

Marigold 9907

Braided from volumised and twisted electrical grade fibreglass yarns, Marigold 9907 is impregnated with a special blend of graphite, a proprietary break-in lubricant and corrosion inhibitors. This highly durable packing is perfect for high temperature applications which require very low friction during start-up and operation.



Marigold 9907 exhibits very good computability with a range of media (including mild acids and alkalis, water, salt water, dry industrial air, combustion gases, petroleum, synthetic oils and solvents) but is not used with steam.

This quality grade of pump and valve packing is used in centrifugal, rotary and reciprocating pumps as well as in valve service and other static applications. As these applications each exert different demands on the packing, the TDS should be checked prior to installation.



Associated Gaskets

Brisbane: 07 3257 1144
Melbourne: 03 9768 3113
Newcastle: 02 4967 7677

Phone: 1300 098 060
Web: www.aga.us.com.au

Perth: 08 9258 5858
Sydney: 02 9774 3333
Wollongong: 02 4272 4800