



Associated Gaskets



### 3100 PVC Soft Grade Foam Tape

AG's 3100 series foam is a soft, highly conformable, low density closed cell foam with an acrylic adhesive on one side. Black in colour, this material forms a water-tight seal at less than 30% compression making it ideal for soft-sealing applications with narrow flange widths or low bolt compression. 3100 PVC Foam Tape offers good resistance to dilute acids and alkalis and UV allowing it to offer long service life. It is manufactured with a swirl free construction allowing it to be drilled through after application. It is capable of sealing in applications where temperatures range from -40°C to 80°C.



| Grade | Thickness | Grade | Thickness |
|-------|-----------|-------|-----------|
| 3103  | 3.2mm     | 3109  | 9.5mm     |
| 3105  | 4.8mm     | 3112  | 12.7mm    |
| 3106  | 6.4mm     | 3119  | 19mm      |

Max roll width 1300mm wide, other colours, sizes and thicknesses available upon request.

### 6100 Neoprene Sponge Tape

6100 series Neoprene Sponge Tape is manufactured from a tough yet conformable grade of neoprene sponge which is coated on one side with an aggressive acrylic based adhesive. This allows 6100 Neoprene sponge tape to adhere to a wide range of surfaces and to maintain adhesive power throughout its long service life. This medium density sponge offers quick recovery from compression coupled with excellent oil, heat, ozone and UV resistance. 6100 Neoprene Sponge tape is utilised in applications where temperatures range from -15°C to 105°C and carries UL recognised self-extinguishing certifications and MIL spec rated flame retardancy capabilities.



| Grade | Thickness | Grade | Thickness |
|-------|-----------|-------|-----------|
| 6102  | 2mm       | 6109  | 9mm       |
| 6103  | 3mm       | 6112  | 12mm      |
| 6105  | 4.8mm     | 6119  | 19mm      |
| 6106  | 6mm       |       |           |

Max roll width 1000mm wide, other colours, sizes and thicknesses available upon request.

## PVC & Neoprene Single Sided Adhesive Sponge Tapes

By combining ease of use with their ability to affect a long lasting, durable seal, AG's range of single sided foam/sponge tapes have proven incredibly popular for a wide variety of sealing applications. This page is designed to provide a brief overview of our two most requested styles which both offer outstanding versatility.

Both our 3100 & 6100 adhesive tapes are closed cell grades which will seal a variety of liquids in low pressure applications. They are also often used for dust seals and to form protective barriers around sensitive electronic equipment and components.



AG's full range of foam/sponge adhesive tapes encompasses both open cell and closed cell styles and is comprised of materials made from a wide variety of rubber and plastic base materials. We couple this enormous range of materials with our extensive fabrication facilities and expertise to offer you the exact, customised solution you require.

All of AG's adhesive sponge tapes are available slit to custom width or in cut component form. We can also layer to achieve greater thicknesses and provide kiss-cut components for easy, labour-saving installation. For more information on the broad range of customisation options available, please contact your local AG branch.

**Brisbane:** 07 3257 1144  
**Melbourne:** 03 9768 3113  
**Newcastle:** 02 4967 7677

## Associated Gaskets

**Phone:** 1300 098 060  
**Web:** [www.agaus.com.au](http://www.agaus.com.au)

**Perth:** 08 9258 5858  
**Sydney:** 02 9774 3333  
**Wollongong:** 02 4272 4800