




# Vidaflex SD550 Electrical Sleeving




Electrical Insulation Sleeving



Rigid Electrical Boards



Electrical Accessories



Cable, Wire and Conductors

This high quality electrical insulation sleeving is manufactured from continuous glass braided sleeve with a solid and smooth silicone elastomer coating.

Flexible with a high dielectric strength, this UL approved sleeving is constructed from self-extinguishing materials and is used in a range of demanding applications.

SD550 Sleeving displays a high degree of flexibility over a wide temperature range. It is rated for continuous exposure to between -60°C and +180°C.



Standard Sizes				
1mm Ø x 250Mtr	4mm Ø x 250Mtr	8mm Ø x 200Mtr	14mm Ø x 50Mtr	25mm Ø x 50Mtr
2mm Ø x 250Mtr	5mm Ø x 250Mtr	10mm Ø x 100Mtr	16mm Ø x 50Mtr	
3mm Ø x 250Mtr	6mm Ø x 250Mtr	12mm Ø x 100Mtr	20mm Ø x 50Mtr	

Key Specifications	
Temperature	-60°C to +180°C
Inner	Fibreglass Braid
Outer	Silicone
Electrical Strength	4.0 kV (60 Sec. IEC)
Short-Term Temp.	250°C Max.
Flammability	Self Extinguishing
Tolerance on Bore Sizes	
1mm Ø & 3mm Ø	± 0.2mm
4mm Ø to 8mm Ø	± 0.25mm
10mm Ø to 12mm Ø	± 0.5mm
14mm Ø to 25mm Ø	± 1.0mm



AG Sydney  
Head Office  
02 9774 3333

[syd@agaus.com.au](mailto:syd@agaus.com.au)

AG Queensland

07 3257 1144

[bris@agaus.com.au](mailto:bris@agaus.com.au)

AG Victoria

03 9768 3113

[melb@agaus.com.au](mailto:melb@agaus.com.au)

AG Western Australia

08 9258 5858

[perth@agaus.com.au](mailto:perth@agaus.com.au)

AG Newcastle

02 4967 7677

[new@agaus.com.au](mailto:new@agaus.com.au)

AG Wollongong

02 4272 4800

[woll@agaus.com.au](mailto:woll@agaus.com.au)

Visit [agaus.com.au](http://agaus.com.au) for more information and full contact details.