

Weicon Aluminium Repair Stick




Epoxy Repair Sticks



Plastic Metal



Epoxy Adhesives



Putties & Compounds

AG Sydney Head Office 02 9774 3333

syd@agaus.com.au

Specifically designed for making non-rusting repairs and bonding metal parts.

It is particularly suited for use with aluminium, though it can be used on a range of other materials as well.

Designed for repair applications, Weicon Repair Stick Aluminium is often used for making repairs to car bodies, transmission casings and window frames as well as in a wide variety of marine and model making applications.

Weicon Repair Stick Aluminium is aluminium-grey in colour and cures in temperatures between 6°C and 40°C.

They are used to cover gaps up to 15mm (maximum) and, once fully cured, resist temperatures ranging from -50°C to 120°C.

Key Specifications						
Colour	Grey					
Density	1.6 g/cm ³					
Pot Life	4 Minutes					
35% Cure	10 Minutes					
Full Cure	24 Hours					
Shore Hardness	75 Shore D					
Temperature Resistance	-50°C to +120°C					
Avg. Tensile Shear Strength	4.2 N/mm² on Sand Blasted Aluminium					



	Standard Sizes								
	57gm		115gm	ו		cut knead		use	
A	G Queensland	AG	Victoria	AG Weste	ern Australia	AG Newca	stle	AG Wollongong	
0	7 3257 1144	03 9	9768 3113	08 9258 5	858	02 4967 76	677	02 4272 4800	
b	ris@agaus.com.au	mel	b@agaus.com.au	<u>perth@ag</u>	aus.com.au	new@agau	<u>is.com.au</u>	woll@agaus.com.a	<u>u</u>

P

Visit <u>agaus.com.au</u> for more information and full contact details.

