



Weicon Copper Repair Stick

Our Copper Repair Stick has a very quick pot life (of just 3 minutes) which allows for incredibly quick application and adhesion and minimal downtime.

Weicon Repair Stick Copper has been tested in accordance with NSF (non-food compounds registration program) standards and can be used on most surface types incl. metal, many plastics, wood, glass, ceramic, stone and more.

This grade is typically used for the repair of cracks holes and leakages (even on wet or damp surfaces) on:

- Pipe, elbows, fittings and flanges
- Metal gutters
- Water heaters and water tanks
- Hot and cold water piping
- Refrigerating and air conditioning equipment



Epoxy Repair Sticks



Plastic Metal



Epoxy Adhesives





Putties & Compounds

Key Specifications	
Colour	Copper
Density	1.9 g/cm ³
Pot Life	3 Minutes
35% Cure	10 Minutes
Full Cure	24 Hours
Shore Hardness	80 Shore D
Temperature Resistance	-50°C to +120°C
Avg. Tensile Shear Strength	4.8 N/mm ² on Sanded Beech



Standard Sizes	
57gm	115gm



AG Sydney
Head Office
02 9774 3333

syd@agaus.com.au

AG Queensland
07 3257 1144

bris@agaus.com.au

AG Victoria
03 9768 3113

melb@agaus.com.au

AG Western Australia
08 9258 5858

perth@agaus.com.au

AG Newcastle
02 4967 7677

new@agaus.com.au

AG Wollongong
02 4272 4800

woll@agaus.com.au

Visit agaus.com.au for more information and full contact details.