



Weicon Steel Repair Stick



Epoxy Repair Sticks



Plastic Metal



Epoxy Adhesives



Putties & Compounds

The Steel grade of epoxy repair putty featured on this page is designed for making quick and high strength repairs to metal parts and surfaces.

Weicon Repair Stick Steel exhibits excellent adhesion to a wide range of metals (including aluminium, cast iron, brass and stainless steel) and is also used on hard plastics, fibre reinforced materials, wood, derived timber products, glass, ceramics and stone.

It enables quick and easy patching and sealing of cracks, holes, leaks and surface damage on:



- Machine parts, tanks and conduit pipes
- Vessels, pumps and housings
- Balcony rails and stair railings
- Stripped threads
- Other applications in the DIY and household sectors



Key Specifications	
Colour	Dark Grey
Density	2 g/cm ³
Pot Life	4 Minutes
35% Cure	10 Minutes
Full Cure	36 Hours
Shore Hardness	75 Shore D
Temperature Resistance	-50°C to +120°C
Avg. Tensile Shear Strength	4.1 N/mm ² on Sandblasted Steel



Standard Sizes	
57gm	115gm



AG Sydney
Head Office
02 9774 3333
syd@agaus.com.au

AG Queensland
07 3257 1144
bris@agaus.com.au

AG Victoria
03 9768 3113
melb@agaus.com.au

AG Western Australia
08 9258 5858
perth@agaus.com.au

AG Newcastle
02 4967 7677
new@agaus.com.au

AG Wollongong
02 4272 4800
woll@agaus.com.au

Visit agaus.com.au for more information and full contact details.