



Weicon VA 1401 Super Glue Info Sheet



Cyanoacrylate Adhesives

A universal adhesive that is particularly well suited to bonding fabric, paper, cardboard, foam rubber and solid elastomers in addition to a wide range of metals, plastics and rubbers.

VA 1401 Cyanoacrylate has a low viscosity and very fast cure time for near instant adhesion to most substrates.



This industrial-grade super glue is also NSF registered and widely used for bonding in the food and beverage industries.



Cleaners & Degreasers

General Surface Compatibility			
Metal	Highly Compatible	Plastic*	Highly Compatible
Rubber	Highly Compatible	EPDM	Highly Compatible
Wood	Compatible	Balsa Wood	Compatible
Glass / Ceramic	Highly Compatible	Leather	Highly Compatible


*Low Surface Energy Types (e.g. PTFE, Polypropylene, Polyethylene only with special pre-treatment).



Epoxy Adhesives

Standard Sizes			
12gm	30gm	60gm	500gm

Key Specifications	
Max. Gap Coverage	0.15mm
Viscosity	100-150 mPa·s
Temp. Resistance Continuous	-50°C to +120°C
Initial Adhesion	
To Aluminium	2 - 10 Seconds
To NBR Rubber	<5 Seconds
Shear Strength	
Sand-Blasted Steel	22 N/mm ²
Rigid PVC	14 N/mm ²
ABS	13 N/mm ²
NBR	>8 N/mm ²



Primers & Accessories

AG Sydney
Head Office
02 9774 3333

syd@agaus.com.au

AG Queensland
07 3257 1144

bris@agaus.com.au

AG Victoria
03 9768 3113

melb@agaus.com.au

AG Western Australia
08 9258 5858

perth@agaus.com.au

AG Newcastle
02 4967 7677

new@agaus.com.au

AG Wollongong
02 4272 4800

woll@agaus.com.au

Visit agaus.com.au for more information and full contact details.