



# Weiconlock AN 302-43

Weiconlock AN 302-43 is a low viscosity, medium strength grade designed for threadlocking applications.

This high quality anaerobic adhesive is DVGW tested for use in gas applications and also has KTW approval for drinking water installations.

Once a threaded connection is sealed with AN 302-43 it can be easily disassembled with normal tools.

Weiconlock 302-43 is blue in colour and has a low viscosity that allows for fast application to threads up to M 36 in size.



Manufactured in Germany, this thread locking glue is available in a selection of sizes to suit your requirements.



Key Specifications	
Colour	Blue
Threads Up To	M 36
Viscosity	2,000 - 7,000 mPa·s
Breakaway Strength (Thread)	17 - 22 Nm
Shear Strength	9 - 13 N/mm <sup>2</sup>
Handling Strength	10 - 20 Minutes
Temp. Resistance	-60°C to +150°C

### Standard Sizes

- 3ml
- 20ml
- 50ml
- 200ml



**Weiconlock Threadlockers & Instant Gaskets**



**Cleaners and Surface Preparation**



**MS Polymer Adhesives & Sealants**



**Gasket & Sealing Tapes**

AG Sydney  
Head Office  
02 9774 3333

[syd@agaus.com.au](mailto:syd@agaus.com.au)

AG Queensland

07 3257 1144

[bris@agaus.com.au](mailto:bris@agaus.com.au)

AG Victoria

03 9768 3113

[melb@agaus.com.au](mailto:melb@agaus.com.au)

AG Western Australia

08 9258 5858

[perth@agaus.com.au](mailto:perth@agaus.com.au)

AG Newcastle

02 4967 7677

[new@agaus.com.au](mailto:new@agaus.com.au)

AG Wollongong

02 4272 4800

[woll@agaus.com.au](mailto:woll@agaus.com.au)

Visit [agaus.com.au](http://agaus.com.au) for more information and full contact details.