

Weiconlock AN 305-77



Weiconlock
Threadlockers &
Instant Gaskets



Cleaners and Surface Preparation



MS Polymer Adhesives & Sealants



Gasket & Sealing Tapes

AG Sydney Head Office 02 9774 3333

syd@agaus.com.au

Weiconlock AN 305-77 is a high quality grade of anaerobic adhesive designed specifically for pipe and thread sealing applications.

Weiconlock AN 305-77 boasts the added benefit of being BAM approved for use in oxygen sealing installations and both DVGW and AGA (Australian Gas Association) approved for use in gas line sealing.

This permanent sealing adhesive is designed for larger threaded joints or pipes up to M 80 (R3").

It has a high viscosity for accurate application and cures with a medium amount of strength which means that connections can be disassembled with the aid of normal tools.

Key Specifications	
Colour	Yellow
Threads Up To	M 80
Viscosity	24,000 - 70,000 mPa·s
Breakaway Strength (Thread)	18 - 22 Nm
Shear Strength	6 - 13 N/mm²
Handling Strength	15 - 30 Minutes
Temp. Resistance	-60°C to +150°C

Standard Sizes

- 50ml
- 200ml
- 300ml











AG Queensland AG Victoria AG Western Australia AG Newcastle AG Wollongong

07 3257 1144 03 9768 3113 08 9258 5858 02 4967 7677 02 4272 4800

bris@agaus.com.au melb@agaus.com.au perth@agaus.com.au new@agaus.com.au woll@agaus.com.au