



SECIALISED TAPES AND LABELS



3M 2308 Performance Masking Tape

3M 2308 Performance Masking Tape is a general-purpose grade of high quality masking tape designed for holding, bundling, sealing and general paint masking applications. This tape is constructed from a natural coloured (beige) crepe paper backing with a pressure-sensitive rubber based adhesive.

3M 2308 Performance Masking Tape provides instant adhesion for fast, easy application and good holding power that resists lifting or curling. The crepe paper backing on this tape is highly conformable which allows it to maintain shape integrity when applied around corners. 2308 Masking Tape is easy to tear by hand, silver resistant and also exhibits good paint hold-out that resists bleed-through.

3M 2308 Performance Masking Tape has controlled unwind which allows it to be dispensed evenly and makes it less likely to tear off when it is applied using paper dispensers. This tape has also been tested and found to meet the requirements of ASTM D 6123 / D 6123M-97.

3M 2308 can become very difficult to remove if subjected to prolonged outdoor exposure.

Properties

Total Thickness (ASTM D-3652)	0.13mm (5.3 Mil)
Adhesion to Steel (ASTM D-3330)	38 N / 100mm (35 oz./in)
Tensile Strength (ASTM D-3759)	385 N / 100mm (22 lbs./in width)
Temperature Resistance	Up to 121°C (250°F) for 30 Min.
Elongation at Break (ASTM D-3759)	10%

Availability

Associated Gaskets slits 3M 2308 Performance Masking Tape in-house and can provide it in whatever width you require (standard widths are also listed below).

Standard roll widths: 6mm, 9mm, 12mm, 15mm, 18mm, 21mm, 24mm

Standard roll length: 55mtrs.

3M is a registered Trademark of 3M.

Visit: www.agaus.com.au

Phone: 1300 098 060

Important

This information should not be treated as a substitute for specific technical advice. AG does not offer such advice and cannot warrant the performance or suitability of products for particular applications.

Rev: V000640 7035R00316AGDOCg