



Adhesive PVC Sponge Tape 3100 Series



3100 Series Adhesive PVC Sponge Tape is a soft, highly conformable, low-density, closed cell sponge with an acrylic adhesive on one side. This tape will form a watertight seal at less than 30% compression, which makes it ideal for sealing applications for flanges with low compression loads, narrow facings and irregular or curved surfaces.

PVC Sponge Tape offers good resistance to diluted acids and UV, which allows it to be used in a range of indoor and outdoor applications whilst still maintaining a long service life. It is often used for sealing low pressure flanges, hatch & door seals, expansion joints, and can also be used to cushion or protect surfaces from damage.

Technical Data:

Colour	Grey
Adhesive	Acrylic
Temperature Range	-40°C to +80°C
Density	Low
Compression	Excellent
Recovery	Good
UV Resistance	Excellent
Resistance to weathering	Excellent

Applications:

- Cabinet and hatch seals
- Expansion joints
- Door and window seals
- Surface edge protection
- Low pressure sealing
- Weather strips
- Light and dust seals



Availability:

3100 Series Tape is available in thicknesses ranging from 3mm to 19mm, in standard widths or can be slit to suit your requirements.

AG also keep an extensive range of sponges and foams in materials such as Neoprene, EPDM and Silicone, as well as specialised electrical products and materials.

For more information on these products and many more, please visit our website or call your nearest AG branch.

Visit: www.agaus.com.au

Phone: 1300 098 060

Important

This information should not be treated as a substitute for specific technical advice. AG does not offer such advice and cannot warrant the performance or suitability of products for particular applications.