

CONTAFEL® H 0865

Description

CONTAFEL® H 0865 consists of polyester fleece impregnated with a special varnish containing carbon black.

Properties

CONTAFEL® H 0865 is highly flexible and absorbent.

Application

CONTAFEL® H 0865 is used e. g. as corona protection on coils for high voltage machines in VPI as well as Resin Rich process.

Materials

CONTAFEL® H 0865 consists of polyester fleece impregnated with a special varnish containing carbon black.

Format

Rolls: max. width 950 mm

Tapes: from 20 mm width upwards

Storability

CONTAFEL® H 0865 can be stored unlimited under normal conditions (20° C, 50 % r. h.)

Technical Data

Properties	Test Method	Unit	Min. Value
Nominal Thickness	DIN 863	mm	0.12
Tolerance	DIN 863	mm	± 0.02
Total Substance	IPV no. 4	g/m ²	110 ± 11
Tensile Strength	DIN 53455	N/10mm	≥ 40
Surface Resistance (square electrode configuration)	IEC 93	Ohm/square	200 ± 50

ISOVOLTA AG, A Constantia Iso AG Company



Associated Gaskets
Quality First Solutions

THIS INFORMATION SHOULD NOT BE TREATED AS A SUBSTITUTE FOR SPECIFIC TECHNICAL ADVICE. ASSOCIATED GASKETS DOES NOT GIVE SUCH ADVICE AND CANNOT WARRANT THE PERFORMANCE OR SUITABILITY OF PRODUCTS FOR PARTICULAR APPLICATIONS.

⇒ VISIT OUR WEB SITE WWW.AGAUS.COM.AU ⇐