

CONTAFEL® H 2014

Description

CONTAFEL® H 2014 consists of polyester fleece impregnated with a special varnish containing carbon black.

Properties

CONTAFEL® H 2014 is highly flexible and absorbent.

Application

CONTAFEL® H 2014 is used e. g. as corona protection on coils for high voltage machines in VPI as well as Resin Rich process.

Materials

CONTAFEL® H 2014 consists of polyester fleece impregnated with a special varnish containing carbon black.

Format

Rolls: max. width 950 mm

Tapes: from 20 mm width upwards

Storability

CONTAFEL® H 2014 can be stored unlimited under normal conditions (20°C, 50% r. h.)

Technical Data

Properties	Test Method	Unit	Min. Value
Nominal Thickness	DIN 863	mm	0.10
Tolerance	DIN 863	mm	± 0.02
Total Substance	IPV no. 4	g/m ²	65 ± 15
Tensile Strength	DIN 53455	N/10mm	≥ 28
Surface Resistance (square electrode configuration)	IEC 93	Ohm/square	1000 ± 500

ISOVOLTA AG, A Constantia Iso AG Company



Quality first solutions

WEB SITE www.agaus.com.au

THIS INFORMATION SHOULD NOT BE TREATED AS A SUBSTITUTE FOR SPECIFIC TECHNICAL ADVICE. ASSOCIATED GASKETS DOES NOT GIVE SUCH ADVICE & CANNOT WARRANT THE PERFORMANCE OR SUITABILITY OF PRODUCTS FOR PARTICULAR APPLICATIONS.

EPB3025R11108AGDOC7

MELBOURNE
 Ph: 03-9768-3113
 Fax: 03-9768-3112
 melb@agaus.com.au

BRISBANE
 Ph: 07-3257-1144
 Fax: 07-3257-1392
 bris@agaus.com.au

AG HEAD OFFICE
 Ph: 61 (0)2 9774-3333
 Fax: 61 (0)2 9774-1100
 sydsales@agaus.com.au

WOLLONGONG
 Ph: 02-4272-4800
 Fax: 02-4272-4445
 woll@agaus.com.au

NEWCASTLE
 Ph: 02-4967-7677
 Fax: 02-4968-9496
 new@agaus.com.au