

# Marigold 3000N Packing

**Service** : Rotating & Static  
**Application** : Pumps & Valves  
**Product Type** : Braided Packing  
**Material** : Acrylic Blended Fibres



## Description

Marigold Style 3000N Packing is braided from continuous acrylic blended fibres, then thoroughly impregnated with a 100% PTFE dispersion. Style 3000N is non-staining and non-contaminating with excellent heat dissipation properties.

Designed for use where contamination from break-in lubricants is not permitted, Marigold 3000N is a durable packing suitable for general service applications such as centrifugal, rotary, and reciprocating pumps, as well as valve service and static seals.

Construction : Interlock Braid  
Temperature Rating : 260°C  
pH Range : 0 - 12  
Shaft Speed Rating : 11.1 mps / 2200 fpm  
Pressure Rating : 34.5 bar / 500 psi

## Applications

Centrifugal, Rotary, and Reciprocating Pumps, as well as Valve Service and other static applications

## Chemical Resistance

Suitable for: - Mild Acids & Alkalis; Air - Dry Industrial; Ammonia Gas; Steam; Water;  
Salt Water/Brine; Petroleum & Synthetic Oils; Aliphatic & Aromatic Solvents

## Yield Information\*

SQ. Section	3.2mm	4.8mm	6.4mm	8.0mm	9.5mm	11mm	12.7mm	14mm	16mm	19mm	22mm	25.4mm
Metres / kg	63.6	36.8	20.1	13.4	8.0	6.3	4.6	3.9	3.2	2.3	1.8	1.4

\*Yields are subject to deviation due to industry accepted tolerance and density variations



**Phone: 1300 098 060**

**Web: [www.agaus.com.au](http://www.agaus.com.au)**

REV: 3-1-2014 V000334 0000R10514AGDOCg

THIS INFORMATION SHOULD NOT BE TREATED AS A SUBSTITUTE FOR SPECIFIC TECHNICAL ADVICE. ASSOCIATED GASKETS DOES NOT GIVE SUCH ADVICE & CANNOT WARRANT THE PERFORMANCE OR SUITABILITY OF PRODUCTS FOR PARTICULAR APPLICATIONS.

**Associated Gaskets Pty Ltd providing Quality first solutions**