

Marigold 3000T Packing

Service : Rotating & Static
Application : Pumps & Valves
Product Type : Braided Packing
Material : Acrylic Blended Fibres



Description

Marigold 3000T is braided from continuous Acrylic blended fibre and impregnated with PTFE and a proprietary inert lubricant. Style 3000T packing is also a non-staining and non-contaminating with excellent heat dissipation properties.

A durable and resilient packing for general service applications such as centrifugal, rotary, and reciprocating pumps as well as valve service. Our proprietary lubricant is used for extremely low friction at startup and during operation.

Construction : Interlock Braid
Temperature Rating : 260°C
pH Range : 2 - 12
Shaft Speed Rating : 11.2 mps / 2200 fpm
Pressure Rating : 34.5 bar / 500 psi

Applications

Centrifugal, Rotary, and Reciprocating Pumps, as well as Valve Service

Chemical Resistance

Suitable for: - Mild Acids & Alkalis; Air - Dry Industrial; Ammonia Gas; Steam; Water;
Salt Water/Brine; Petroleum & Synthetic Oils; Aliphatic & Aromatic Solvents

Yield Information*

SQ. Section	3.2 mm	4.8 mm	6.4 mm	8 mm	9.5 mm	12.7 mm	16 mm	19 mm	22 mm	25.4 mm
Metres / kg	59.0	28.8	20.8	11.1	7.7	4.8	2.7	2.1	1.7	1.1

*Yields are subject to deviation due to industry accepted tolerance and density variations



Phone: 1300 098 060

Web: www.agaus.com.au

REV: 1-2-2006

1125R40813AGDOCg

THIS INFORMATION SHOULD NOT BE TREATED AS A SUBSTITUTE FOR SPECIFIC TECHNICAL ADVICE. ASSOCIATED GASKETS DOES NOT GIVE SUCH ADVICE & CANNOT WARRANT THE PERFORMANCE OR SUITABILITY OF PRODUCTS FOR PARTICULAR APPLICATIONS.

Associated Gaskets Pty Ltd providing Quality first solutions