

Marigold 3030INA Packing

Service : Static
Application : Valves Only
Product Type : Braided Packing
Material : Inconel® Wire Fibreglass



Description

Marigold 3030INA is braided from Inconel® wire inserted fibreglass over a proprietary core with a surface coating of blended graphite. Style 3030INA packing also contains a corrosion inhibitor to internally protect the valve from oxidation. Ideally suited for high temperature and pressure valve stem applications for steam, gas and hydrocarbons and also as an expansion joint packing.

Construction : Braid Over Core
Temperature Rating : 455°C in Air
649°C in Steam
pH Range : 2 - 13
Shaft Speed Rating : Static Applications Only
Pressure Rating : 207 bar / 3000 psi

Applications

Valve Service and other static applications

Chemical Resistance

Suitable for: - Strong Acids & Alkalis; Air - Dry Industrial; Steam; Water; Salt Water/Brine;
Petroleum & Synthetic Oils; Aliphatic & Aromatic Solvents

Yield Information*

SQ. Section	3.2mm	4.8mm	6.4mm	8.0mm	9.5mm	11mm	12.7mm	14mm	16mm	19mm	22mm	25.4mm
Metres / kg	73.0	26.1	18.7	12.0	8.7	6.8	4.9	3.9	3.0	2.2	1.6	1.2

*Yields are subject to deviation due to industry accepted tolerance and density variations



Phone: 1300 098 060

Web: www.agaus.com.au

REV: 3-1-2014 V000334 0000R20413AGDOCg

THIS INFORMATION SHOULD NOT BE TREATED AS A SUBSTITUTE FOR SPECIFIC TECHNICAL ADVICE. ASSOCIATED GASKETS DOES NOT GIVE SUCH ADVICE & CANNOT WARRANT THE PERFORMANCE OR SUITABILITY OF PRODUCTS FOR PARTICULAR APPLICATIONS.

Associated Gaskets Pty Ltd providing Quality first solutions