



Marigold 344T Packing



Marigold 344T packing is braided from 100% PTFE filament that is impregnated with a PTFE suspensoidal blocking agent and a proprietary break in lubricant. Flattened into a dense yet soft tape, it is commonly used where a conformable and chemical resistant seal is required. Style 344T is also available without the break in lubricant on request.

Technical Data:

Material	100% PTFE
Construction	Hollow Braid
Style Number	344T
Service	Gasketing
Temperature Rating	260°C
pH Rating	0 - 14
Shaft Speed Rating	N/A
Pressure Rating	300 PSI / 20 BAR

Availability:

Marigold 344T packing is available in a range of sizes and lengths.

Associated Gaskets sell packing by the roll, by the metre, or can cut to suit your requirements. Custom sizes and other styles are also available on request.



Packing can also be pre-formed to suit your shaft size and packaged in sets for ease of installation. Pre-formed graphite ribbon packing rings are also available for more critical applications. AG's fabrication department can also cut, mitre, and chamfer these rings to your exact dimensions. For more information on these products and many more, please visit our website or call your nearest AG branch.

Visit: www.agaus.com.au

Phone: 1300 098 060

Important

This information should not be treated as a substitute for specific technical advice. AG does not offer such advice and cannot warrant the performance or suitability of products for particular applications.