

# Marigold 345 Packing

**Service** : Rotating & Static  
**Application** : Pumps & Valves  
**Product Type** : Braided Packing  
**Material** : Flax & Ramie Fibres



## Description

Braided from a proprietary blend of high quality flax and ramie yarns, Marigold 345 is thoroughly impregnated with PTFE and a proprietary inert lubricant. The unique braiding technique and deep PTFE impregnation makes Style 345 easy to cut and install, with excellent braid retention and conformability. Style 345 is also long lasting, corrosion resistant, and is ideally suited for use in most saltwater/freshwater applications including stern tubes and rudder posts.

Construction : Plait Braid  
Temperature Rating : 200°C  
pH Range : 5 - 11  
Shaft Speed Rating : 6.1 mps / 1200 fpm  
Pressure Rating : 20.7 bar / 300 psi

## Applications

Rotary, Reciprocating and Centrifugal Pumps, as well as Valve Service & other Static applications

## Chemical Resistance

Suitable for: - Water; Salt Water/Brine; Petroleum & Synthetic Oils

## Yield Information\*

SQ. Section	3.2 mm	4.8 mm	6.4 mm	8 mm	9.5 mm	12.7 mm	16 mm	19 mm	22 mm	25.4 mm
Metres / kg	60.3	27.4	16.7	12.7	8.7	5.1	3.5	2.1	1.8	1.2

\*Yields are subject to deviation due to industry accepted tolerance and density variations



**Phone:** 1300 098 060

**Web:** [www.agaus.com.au](http://www.agaus.com.au)

REV: 22-2-2006

0000R20813AGDOCg

THIS INFORMATION SHOULD NOT BE TREATED AS A SUBSTITUTE FOR SPECIFIC TECHNICAL ADVICE. ASSOCIATED GASKETS DOES NOT GIVE SUCH ADVICE & CANNOT WARRANT THE PERFORMANCE OR SUITABILITY OF PRODUCTS FOR PARTICULAR APPLICATIONS.

**Associated Gaskets Pty Ltd providing Quality first solutions**