

Marigold 8000T-WO Packing

Service : Rotating & Static
Application : Pumps & Valves
Product Type : Braided Packing
Material : Proprietary



Description

Marigold 8000T-WO is braided from a unique combination of self lubricating, abrasion resistant yarns which stand up to high shaft speeds, without shaft scoring, while remaining durable and conformable. Style 8000T-WO is designed for use in Mining, Pulp and Paper, and Water treatment applications.

Construction : Interlock Braid
Temperature Rating : 260°C
pH Range : 0 - 14*
Shaft Speed Rating : 15.2 mps / 3,000 fpm
Pressure Rating : Valves - 124 bar / 1,800 psi
Pumps - 20.7 bar / 300 psi

* Except for Strong Oxidisers

Applications

Centrifugal, Rotary, and Reciprocating Pumps, as well as Valve Service and other static applications

Chemical Resistance

Suitable for: - Strong Acids & Alkalis; Steam; Air - Dry Industrial; Ammonia Gas; Water; Salt Water/Brine; Bromine Gas; Chlorine Gas; Petroleum & Synthetic Oils; Aliphatic & Aromatic Solvents

Yield Information*

SQ. Section	3.2mm	4.8mm	6.4mm	8mm	9.5mm	11mm	12.7mm	16mm	19mm	22mm	25.4mm
Metres / kg	47.5	26.1	14.7	10.0	7.3	5.3	3.8	2.5	1.8	1.3	1.0

*Yields are subject to deviation due to industry accepted tolerance and density variations



Phone: 1300 098 060

Web: www.agaus.com.au

REV: 18-8-2008 V000334 0000R10414AGDOCg

THIS INFORMATION SHOULD NOT BE TREATED AS A SUBSTITUTE FOR SPECIFIC TECHNICAL ADVICE. ASSOCIATED GASKETS DOES NOT GIVE SUCH ADVICE & CANNOT WARRANT THE PERFORMANCE OR SUITABILITY OF PRODUCTS FOR PARTICULAR APPLICATIONS.

Associated Gaskets Pty Ltd providing Quality first solutions