

Marigold 921G Packing

Service : Rotating & Static
Application : Pumps & Valves
Product Type : Braided Packing
Material : Flax and Ramie Fibres



Description

Marigold Style 921G Packing is braided from a long lasting blend of Flax and Ramie fibres which are thoroughly lubricated with a proprietary tallow and wax blend. A surface coating of high purity graphite is added to further reduce friction. Style 921G is a low friction, general service packing used extensively on shipboard applications for stern tubes, rudderposts, and water pumps. This packing is especially resistant to cold water, seawater, and cold oils, but is also used in a variety of other applications in the marine, pulp and paper, and wastewater industries.

Construction : Plait Braid
Temperature Rating : 104°C
pH Range : 5 - 9
Shaft Speed Rating : 6.1 mps / 1200 fpm
Pressure Rating : 10.3 bar / 150 psi

Applications

Centrifugal, Rotary, and Reciprocating Pumps, as well as Valve Service and other static applications

Chemical Resistance

Suitable for: - Cold Water; Salt Water/Brine

Yield Information*

SQ. Section	3.2mm	4.8mm	6.4mm	8.0mm	9.5mm	11mm	12.7mm	14mm	16mm	19mm	22mm	25.4mm
Metres / kg	62.9	33.5	21.4	12.0	9.1	7.6	6.0	4.7	3.3	2.4	2.0	1.4

*Yields are subject to deviation due to industry accepted tolerance and density variations



Phone: 1300 098 060

Web: www.agaus.com.au

REV: 3-1-2014 V000334 0000R10514AGDOCg

THIS INFORMATION SHOULD NOT BE TREATED AS A SUBSTITUTE FOR SPECIFIC TECHNICAL ADVICE. ASSOCIATED GASKETS DOES NOT GIVE SUCH ADVICE & CANNOT WARRANT THE PERFORMANCE OR SUITABILITY OF PRODUCTS FOR PARTICULAR APPLICATIONS.

Associated Gaskets Pty Ltd providing Quality first solutions