Technical Data...

Red Fibre Sheet

Red vulcanized fibre is a vintage material of late 19th century technology, which amazingly still has uses today.

Suitable only for non critical applications.

Density	:	~1.4 gms cm³
Colour	:	Red
Temperature Range	:	10°C to ~85°C
Construction	:	Cellulose Paper
Binder	:	Cellulose
Water Absorption	:	High
Sheet Size	:	2000mm x 1200mm
Availability	:	0.8mm, 1.5mm & 3mm Thick

- Resilient & Tough
- Long Wearing
- Good Tear Resistance
- Good Impact strength
- Suitable for Forming and Punching
- Electrically Insulating in Dry, Low Humidity Environments
- Fabricate using: - Guillotine, Saw, Drill and Punching Press

Quality first solutions

www.agaus.com.au

THIS INFORMATION SHOULD NOT BE TREATED AS A SUBSTITUTE FOR SPECIFIC TECHNICAL ADVICE. ASSOCIATED GASKETS DOES NOT GIVE SUCH ADVICE & CANNOT WARRANT THE PERFORMANCE OR SUITABILITY OF PRODUCTS FOR PARTICULAR APPLICATIONS.

GPB0310R10711AGDOC8

AG MELBOURNE
Ph: 03-9768-3113
Fax: 03-9768-3112
melb@agaus.com.au

AG BRISBANE
Ph: 07-3257-1144
Fax: 07-3257-1392
bris@agaus.com.au

AG HEAD OFFICE
Ph: 61 (0)2 9774-3333
Fax: 61 (0)2 9774-1100
sydsales@agaus.com.au

AG WOLLONGONG
Ph: 02-4272-4800
Fax: 02-4272-4445
woll@agaus.com.au

AG NEWCASTLE
Ph: 02-4967-7677
Fax: 02-4968-9496
new@agaus.com.au