



Weicon Adhering Grease – Extra Strong

Weicon Adhering Grease – Extra Strong is a special lubricant and corrosion protection spray that can even be used for underwater applications. This high quality lubricant provides effective protection against aggressive liquids (such as sea water or waste water) in marine applications.

Adhering Grease is used on:

- Roller and slide bearings (even in mixed friction operation)
- Joints, levers, slideways, spindles and splined shafts
- Open gearing (such as gear rims)
- Work gear pairs, chains and wire cable at all slide speeds where grease lubrication is permitted

Properties

| | |
|------------------------|------------------|
| Colour | Beige |
| Odour | Almost Odourless |
| Temperature Resistance | -25°C to +80°C |
| Minimum Shelf Life | 24 Months |

Preparation of the Surface

Clean and degrease surfaces prior to application (Weicon Cleaner S or Weicon Surface Cleaner may be suitable for this task). Bring can to room temperature (if stored below) before use.

Processing

Shake can thoroughly before use until mixing ball can be clearly heard. Spray Weicon Adhering Grease onto the cleaned and dry surface from a distance of about 15cm.

Storage

Cans of Weicon Adhering Grease – Extra Strong Spray should be stored away from direct sunlight and not exposed to temperatures exceeding 50°C. Minimum shelf life is 24 months.

Availability

Weicon Adhering Grease – Extra Strong Spray is available in 400ml aerosol cans.

Visit: www.agaus.com.au

Phone: 1300 098 060

Important

This information should not be treated as a substitute for specific technical advice. AG does not offer such advice and cannot warrant the performance or suitability of products for particular applications.