



TECHNICAL LIQUIDS



Weicon Bio-Cut Fluid

Weicon Bio-Cut Fluid is a specialised cooling lubricant designed to enable higher speeds and longer performance from cutting tools. This specially formulated lubricant is not water-miscible and is primarily used for the processing of low to high alloyed steel, stainless steel, aluminium and nonferrous heavy metal.

This high performance product is free of mineral oils and is fully biodegradable. Weicon Bio-Cut Fluid is typically used on drilling, turning, milling, reaming, sewing, punching and thread cutting equipment where it enhances performance and extends service life. Machines and fixtures treated with Bio-Cut Fluid are also protected against corrosion for extended periods.

Properties

Colour	Clear
Odour	Almost Odourless
Temperature Resistance	Up to 200°C
Minimum Shelf Life	24 Months

Compatible With

Weicon WSD 400 Pressurised air Dispenser

Processing

Apply suitable amounts of undiluted Bio-Cut to the work piece by brushing, dropping or spraying.

Storage

Containers of Weicon Bio-Cut Fluid should be stored in their closed, original container away from direct solar radiation and not exposed to temperatures exceeding 50°C. Minimum shelf life is 24 months.

Availability

Weicon Bio-Cut Fluid is available in 500ml Squeeze Bottles as well as 5L, 10L and 30L bulk liquid containers.

Visit: www.agaus.com.au

Phone: 1300 098 060

Important

This information should not be treated as a substitute for specific technical advice. AG does not offer such advice and cannot warrant the performance or suitability of products for particular applications.