



TECHNICAL SPRAYS



Weicon PTFE Fluid Spray NSF

Weicon PTFE Fluid Spray NSF is a specially formulated dry film lubricating spray designed for sensitive areas. Somewhat similar to our Weicon PTFE Spray, PTFE Fluid Spray NSF also offers excellent lubrication and a strong anti-adhesive effect but also meets the stringent requirements of NSF which allows it to be used in many areas of the food, beverage, pharmaceutical and cosmetic industries.

PTFE Fluid Spray NSF is manufactured with a high proportion of PTFE which allows it to offer exceptional lubrication of treated surfaces to reduce friction and protect against unwanted adhesion. PTFE Fluid Spray is grease-free and adheres well to all metal, plastic and wooden surfaces for long lasting performance. The coating created by this lubricating spray repels dirt, dust and water and is also resistant to oils, greases and many chemicals.

Typical Applications

- Sliding and Running Rails and Guides
- Conveyor Belts, Transport Rollers and Slides
- Tilt Mechanisms
- Locks and Hinges
- Cutting Tools and Packaging Machines
- Shafts in Plastic Bearings
- As a Coating for Solid Seals
- As an Assembly Aid for Seal Packs

Properties

Colour	Whitish / Transparent
Odour	Almost Odourless
Temperature Resistance	-180°C to +260°C
Minimum Shelf Life	24 Months

Approvals & Certifications

NSF Approved

Preparation of the Surface

No special surface pre-treatment is required.

Storage

Cans of Weicon PTFE Fluid Spray NSF should be stored away from direct sunlight and not exposed to temperatures exceeding 50°C. Minimum shelf life is 24 months.

Availability

Weicon PTFE Fluid Spray is available in 400ml aerosol cans.

Visit: www.agaus.com.au

Phone: 1300 098 060

Important

This information should not be treated as a substitute for specific technical advice. AG does not offer such advice and cannot warrant the performance or suitability of products for particular applications.