



TECHNICAL SPRAYS



Weicon PTFE Spray

Weicon PTFE Spray is a grease free lubricating agent with an anti-adhesive effect. Manufactured from a precision formulation that is based on polytetrafluoroethylene (PTFE), PTFE spray adheres well to all metal, plastic and wood surfaces. As a result of the high percentage of PTFE in the spray, PTFE spray significantly reduces the coefficient of friction on treated surfaces and leaves a coating that resists dirt, dust, water, oils, greases and many chemicals.

PTFE Spray is used in a wide variety of applications and areas. Specific examples include the lubrication of slide rails, conveyor belts, transport rollers, chutes, windows, tipping mechanisms, locks, hinges, cutting tools and plastic bearing shafts. It is also used to create a water resistant coating on paper or cork seals and wherever separating agents containing silicone, or oil or grease based lubricants, are not permitted.

Properties

Colour	Colourless
Odour	Mineral Oil
Temperature Resistance	---
Minimum Shelf Life	24 Months

Preparation of the Surface

Clean and degrease surface.

Processing

Shake can until mixing ball can be heard clearly. Spray on PTFE Spray from a distance of about 20cm. When covering large areas, it is suggested that you pause to shake the can again from time to time. PTFE Spray will be dust dry after about 10 minutes (at a room temperature of approximately 20°C).

Storage

Cans of Weicon PTFE Spray should be stored away from direct sunlight and not exposed to temperatures exceeding 50°C. Minimum shelf life is 24 months.

Availability

Weicon PTFE Spray is available in 400ml aerosol cans.

Visit: www.agaus.com.au

Phone: 1300 098 060

Important

This information should not be treated as a substitute for specific technical advice. AG does not offer such advice and cannot warrant the performance or suitability of products for particular applications.