



TECHNICAL SPRAYS



Weicon Silicone Spray

Weicon Silicone Spray is a high quality lubricant that can be used as a separating agent, general lubricant or as a preservation agent with plastics, rubbers and metals. When used as a separating agent, Silicone Spray creates a durable separating film that exhibits good surface properties.

This versatile lubricating agent is used in a variety of applications. Examples include:

- Preventing the development of adhesive residue in presses and guides.
- Prevent the adhesion of goods on conveyor belts, channels and slides.
- Protecting electrical contacts from moisture.
- Caring for rubber, plastic and metal parts and surfaces.
- Protecting rubber parts from becoming brittle, freezing or adhering.
- Lubricating sunroofs, seat rails, seatbelt rollers and other moving parts.

Properties

Colour	Clear
Odour	Solvent
Temperature Resistance	-50°C to +250°C
Minimum Shelf Life	24 Months

Preparation of the Surface

Clean and degrease the surface to which Silicone Spray will be applied. Weicon Cleaner S, or Surface Cleaner may be suitable for this task.

Processing

Spray Silicone Spray onto the part being treated from a distance of about 25cm.

Storage

Cans of Weicon Silicone Spray should be stored away from direct sunlight and not exposed to temperatures exceeding 50°C. Minimum shelf life is 24 months.

Availability

Weicon Silicone Spray is available in 400ml aerosol cans.

Visit: www.agaus.com.au

Phone: 1300 098 060

Important

This information should not be treated as a substitute for specific technical advice. AG does not offer such advice and cannot warrant the performance or suitability of products for particular applications.